

!  
!!!  
!!

**DS-天和树脂系列**

DS-196P-3

| !      |           |          |          |
|--------|-----------|----------|----------|
| !!! !  | !!! !     | !!! !    | !        |
| !! !   | !         | !        | !        |
| !      | "#\$%&'#! | ()*++!   | "#\$%&'! |
| ,+- .! | " /0!2!   | 344*-44! | "#()&*!  |
| !      | "56!      | ((*(7!   | "#()&*!  |
| ! !    | "56!      | +4*38!   | "#()&*!  |
| !      | "56!      | -*7!     | "#()&*!  |
| !      | 9!        | 84*88!   | "#()&*!  |
| :4 !   | ;! !      | +)! !    | "#()&*!  |

: 凝 为 '\$°C !'+, 中加入 +(' ./0 123 !

!

| !       |         |        |            |
|---------|---------|--------|------------|
| !!! !   | 单!!!位!  | !!! !  | 准!         |
| 巴 尔 度!! | #4567!! | 8+!    | "#*%'8!    |
| 伸强度!    | 0 34!   | 9+!    | "#\$'9(!   |
| 伸弹 !    | 0 34!   | \$'++! | "#\$'9(!   |
| 延伸 !!   | :!      | *+!    | "#\$'9(!   |
| 弯 强度!!  | 0 34!   | %'!    | "#\$'9(!   |
| 弯 弹 !!  | 0 34!   | \$'++! | "#\$'9(!   |
| 冲击 !    | 2;<. !  | (+!    | "#\$'9(!   |
| 变形 度!   | °C!     | ('!    | "#)9*8-\$! |

: 实 境 度 \$\*±\$°C! 对 度 '+±':